

(19)



JAPANESE PATENT OFFICE

(1)

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **07029651 A**

(43) Date of publication of application: **31.01.95**

(51) Int. Cl. **H01R 33/02**
G02B 6/00
G02F 1/1335
G09F 9/00

(21) Application number: **05177097**

(71) Applicant: **SHARP CORP**

(22) Date of filing: **16.07.93**


(72) Inventor: **INOUE KOJI**

(54) **BACKLIGHT DEVICE FOR DISPLAY**

(57) Abstract:

PURPOSE: To dispense with a lead wire guide, and prevent an increase in the number of parts due to a connector having lead wire guide function.

CONSTITUTION: The fluorescent tube coupling section 14 of a connector 11 is coupled to the external surface of the electrode section 8a of a fluorescent tube 8, so as to be freely detachable, and a feed lead wire 10 inserted in the connector 11 is supported on a lead wire bearing section 15. The conductor 10b of the lead wire 10 is detachably coupled to a lead wire coupling section 16, thereby keeping the wire 10 and the tube 8 communicated with each other. According to this construction, the fluorescent tube 8 can be easily changed.



COPYRIGHT: (C)1995,JPO

BEST AVAILABLE COPY